


NORDIC STABIL PLUS




Wood




French Oak Light

4505 000
4504 000



French Oak Natural

4505 001
4504 001



French Oak Dark


4505 002
4504 002

Costa Rica



White

4505 009
4504 009



Medium Brown

4505 010
4504 010



Beige

4505 011
4504 011



Medium Yellow

4505 012
4504 012



Grege

4505 014
4504 014

TECHNICAL DATA	STANDARDS	Nordic Stabil Plus	
		2m	4m
Classification			
Type of floor Covering	ISO 11638 (EN 651)	Heterogeneous Acoustic Vinyl	
Classification	ISO 10874 (EN 685) commercial industrial	Classes: 32 41	
Characteristics			
Total thickness	ISO 24346 (EN 428)	2.50mm	
Wear layer thickness	ISO 24340 (EN 429)	0.35mm	
Total weight	ISO 23997 (EN 430)	1 750g/m ²	
PUR Reinforcement	-	TopClean XP	
Abrasion group	EN 660-2	Group T: ≤ 2mm ³	
Technical performances			
Residual indentation	Average measured value	0.20mm	
	ISO 24343-1 (EN 433) requirement	≤ 0.35mm	
Reaction to fire	EN 13501-1	C _n s1 glued over any A2 _n or A1 _n substrate (concrete) C _n s1 glued over any derivative wood substrate	
Slip resistance	DIN 51130 EN 13893	R9 ≥ 0.3	
Dimensional stability	ISO 23999 (EN 434)	< 0.10%	
Furniture leg	EN 424	No damage	
Castor wheel test	ISO 4918 (EN 425)	No damage	
Curl resultant to heat	ISO 23999 (EN 434)	≤ 8mm	
Electrostatic properties	EN 1815 EN 1081	< 2 kV on concrete R1 > 10 ⁹ ohms	
Chemical resistance	ISO 26987 (EN 423)	High resistance	
Hygiene	-	Does not contribute to infection spreading	
Thermal resistance Underfloor heating	EN ISO 10456	0.05m ² K/W Suitable	
Light fastness	EN ISO 105-B02	≥ 6	
Impact sound reduction		ΔL _w = 18dB	

The above information is subject to modifications for the benefit of further improvement (07/2015).

For more detailed technical information, please contact Tarkett.

NORDIC STABIL PLUS

Main Product Features

- Acoustic, walking and thermic comfort
- Easy and quick to install over an existing or uneven subfloor without levelling compound
- Available in 2m and 4m
- Low cost and easy maintenance with PU protection

Surface Treatment



Sustainability Tag



(1) For all products produced in 2015

Logistics Information



Available in rolls: 2 & 4m
Rolls length: 251m

Laying direction:



General Information



According to European
Classification ISO 10874 (EN 685)



Play with the Room Designer

VINYL HEAVY TRAFFIC

